



4-channel amplifier with 70/100 V and 4 ohms - 240 W/channel, Dante input

The professional audio amplifiers of the axxent TS series are optimised for use in fixed installations. The 4-channel model AX4240TS-D complements this series with an output power of 240 W/channel and 480 W mono bridged per pair. **In addition to the analogue inputs, this model has a Dante digital input for easy networking. The switching power supply saves weight and increases efficiency and power balance.**

Each of the 4 channels offers an independent clip limiter with separate indicators on the front panel. Excellent audio quality throughout the power range is supported in the inputs by special balanced integrated circuits with high common-mode rejection.

In addition to the constant voltage outputs with 70 and 100 V taps, low-impedance outputs are also available.

Galvanic isolation by means of high-quality audio output transformers enables earth-fault monitoring and serves to protect the 100 V lines against accidental contact.

The rated output power is 240 W into 100 V and 4 ohms, or 170 W into 8 ohms per channel. These flexible output configurations make the AX4240TS-D 4-channel amplifier the ideal choice for use in fixed installations. The four amplifier channels can be operated individually or in bridge mode (2x470 ohms and 8 ohms) for power bundling. The only adjustment elements on the front panel are the input level controls. To protect against unintentional or unauthorised adjustment, the control knobs can be removed and replaced with the supplied blanking plugs.

The connections - inputs: analogue balanced XLR and digital with Dante compatibility. Analogue/digital switching is individually selectable for all four channels. All outputs, low impedance and 70 V/100 V, have 10-pin Phoenix screw terminal connectors. Mains voltage input via IEC connector. The robust housing is made of reinforced, powder-coated sheet steel. CE certification for Europe-wide use.

The most important features

- ✓ Output power 4x240 Wrms with all constant voltage output configurations (70/100 V) and with low impedance outputs (4 ohms). In bridge mode 2x470 Wrms at 8 Ohm.
- ✓ Analogue balanced XLR inputs, digital Dante input. All four channels switchable analogue/digital.
- ✓ Euroblock output connector for all outputs.
- ✓ High-quality audio output transformers for galvanic isolation enable earth-fault monitoring and serve to protect against contact with 100 V lines.
- ✓ Two-speed fan with automatic control.
- ✓ Removable knobs and blanking plugs and rear on-off switches for security against unauthorised change of settings.
- ✓ IEC mains socket on the rear of the unit facilitates cabling in the rack.
- ✓ Dimensions: 484 x 88 x 387 mm (WxHxD)
- ✓ Net weight: 15.4 kg without enclosed mains cable
- ✓ Scope of delivery: amplifier, mains cable, 4 blanking plugs
- ✓ European quality product



Technical Data Class AB output stages

Output power 100V (equal for 4 Ohm) Power 1 kHz
THD 1%

single-channel operated 272 W per channel
 two channels operated 262 W per channel
 three channels operated 247 W per channel
 All channels operated together 235 W per channel
 Bridge mode 1-2 (min.8 Ohm) 470 W bridged
 Bridge mode 3-4 (min.8 Ohm) 470 W bridged

Frequency response +0/-2dB

20 Hz 20 kHz

Distortion factor at -1 dB below nominal output power

>0,2%

Intermodulation distortion 60Hz and 7kHz at 4:1, -1dB
below nominal output power

>0,4%

Input sensitivity analogue input at nominal power

0dBu (775 mV)

Voltage Gain, 100V

123x(41.8dB)

Voltage Gain, 4Ohm

38,5x(31.7dB)

Input impedance

10 kOhm unbalanced

20 kOhm balanced

Common mode rejection (1kHz)

>80dB

Signal-to-noise ratio

>90dB

Signal to noise ratio, „A“ weighted

>100dB

Crosstalk

>60dB

Input sensitivity Dante input at nominal power

0dBu (775 mV)

Switch to sensitivity ON

-9dBu(270mV)

Voltage amplification 100V

133x(42.5 dB)

(Sensitivity -9dB)

366x(51.3 dB)

Voltage gain 4 Ohm

41,2x(32.3dB)

(Sensitivity -9dB)

115x(41.2dB)

Sampling rate

48kHz

DA converter

24bit

Input connector, analogue

3-pin XLR female, balanced

Input connector, digital

RJ45 socket, Dante conform

Output connector

10-pole Phoenix terminal connector

4 Ohm, 70 V and 100 V constant voltage

Cooling

2 speed fan

Protective measures

Overload, short circuit, thermal

Mains voltage

230V AC / 50 Hz

Dimensions

483x88x387 mm (WxHxD)

Weight

15.4 kg without packaging and power connection
 cable (enclosed)



OPERATING ELEMENTS BACKSIDE

- 1: Mains switch
- 2: Mains plug connection
- 3: Analogue / Dante switch
- 4: Switch for digital sensitivity 0dB / -9dB
- 5: Ethernet Dante connection
- 6: Dante reset button
- 7: 4x analogue XLR input
- 8: 2x Phoenix 10-pole plug output

OPERATING ELEMENTS FRONTSIDE

- 1: Volume control (each channel)
- 2: Operating display (each channel)
Signal display (each channel)
Limit value display (each channel)
- 3: 2x bridge display (1+2, 3+4 channel)
1x Protect indicator

Performance characteristics (measured with 4-channel operation)

Duty cycle	Power consumption	Current collection	Volt-Ampere	Power factor
IDLE	49W	0.42A	98	0.5
1/8	690W	4.3A	996	0.69
1/3	1079W	6.55A	1492	0.72
1/1	1700W	10A	2255	0.75

Tender text

Four-channel audio power amplifier with constant voltage outputs (70/100 V) and additional low-impedance outputs; rated output power 4x240 W (RMS) into 4 ohms, bridged per amplifier channel pair 470 W into 8 ohms; energy-saving switch-mode power supply, inputs 3-pole XLR connector analogue and RJ45 connector for Dante digital input signal. Outputs: 10-pin Euroblock (Phoenix) screw terminal connections. Two-speed fan, automatically controlled. LED indicators for operation, signal, limit and bridge operation as well as protection function. Adjusters at the front for gain (volume), which can be covered to prevent accidental misuse. Blanking plugs included in delivery. Mains switch on rear of unit; detachable mains cable, IEC plug. Dimensions 483x88 (2U) x 387 mm (WxHxD). Net weight 15.4 kg. The amplifier shall be an axxent model AX4240TS-D.

